


EKU5-T2-20 SPD TYPE T2

ETЭK®

Standard_ IEC/EN61643-11

Product Selection Guide



EKU5-T2-20
2P(1P+N)



EKU5-T2-20
1P+NPE



EKU5-T2-20
3P



EKU5-T2-20
4P(3P+N)




EKU5-T2-20
3P+NPE


Basic circuit diagram




1P




2P




1P+NPE



3P



4P(3P+N)



3P+NPE

SPD Type Reference List

No. of Poles	Max. Continuous Operating AC Voltage				
	150V	275V	320V	385V	440V
1P	EKU5-T2-20-1P150	EKU5-T2-20-1P275	EKU5-T2-20-1P320	EKU5-T2-20-1P385	EKU5-T2-20-1P440
2P(1P+N)	EKU5-T2-20-2P150	EKU5-T2-20-2P275	EKU5-T2-20-2P320	EKU5-T2-20-2P385	EKU5-T2-20-2P440
3P	EKU5-T2-20-3P150	EKU5-T2-20-3P275	EKU5-T2-20-3P320	EKU5-T2-20-3P385	EKU5-T2-20-3P440
4P(3P+N)	EKU5-T2-20-4P150	EKU5-T2-20-4P275	EKU5-T2-20-4P320	EKU5-T2-20-4P385	EKU5-T2-20-4P440
1P+NPE	EKU5-T2-20-1PN150	EKU5-T2-20-1PN275	EKU5-T2-20-1PN320	EKU5-T2-20-1PN385	EKU5-T2-20-1PN440
3P+NPE	EKU5-T2-20-3PN150	EKU5-T2-20-3PN275	EKU5-T2-20-3PN320	EKU5-T2-20-3PN385	EKU5-T2-20-3PN440

With Remote Signaling

1P	EKU5-T2-20-1P150S	EKU5-T2-20-1P275S	EKU5-T2-20-1P320S	EKU5-T2-20-1P385S	EKU5-T2-20-1P440S
2P(1P+N)	EKU5-T2-20-2P150S	EKU5-T2-20-2P275S	EKU5-T2-20-2P320S	EKU5-T2-20-2P385S	EKU5-T2-20-2P440S
3P	EKU5-T2-20-3P150S	EKU5-T2-20-3P275S	EKU5-T2-20-3P320S	EKU5-T2-20-3P385S	EKU5-T2-20-3P440S
4P(3P+N)	EKU5-T2-20-4P150S	EKU5-T2-20-4P275S	EKU5-T2-20-4P320S	EKU5-T2-20-4P385S	EKU5-T2-20-4P440S
1P+NPE	EKU5-T2-20-1PN150S	EKU5-T2-20-1PN275S	EKU5-T2-20-1PN320S	EKU5-T2-20-1PN385S	EKU5-T2-20-1PN440S
3P+NPE	EKU5-T2-20-3PN150S	EKU5-T2-20-3PN275S	EKU5-T2-20-3PN320S	EKU5-T2-20-3PN385S	EKU5-T2-20-3PN440S

Technical Data

SPD classification according to IEC/EN61643-11		T2	T2	T2	T2	T2
Max. continuous operating a.c.voltage	Uc	150V	275V	320V	385V	440V
Max. continuous operating a.c.voltage	Uc(N-PE)	255V	255V	255V	255V	255V
Norminal discharge current (8/20μs)	In	10kA	10kA	10kA	10kA	10kA
Maximum discharge current (8/20μs)	I _{max}	20kA	20kA	20kA	20kA	20kA
Voltage protection level	Up	≤0.8kV	≤1.0kV	≤1.2kV	≤1.45kV	≤1.6kV
Voltage protection level 5kA	Up	≤0.5kV	≤0.8kV	≤1.0kV	≤1.2kV	≤1.4kV
Voltage protection level	Up(N-PE)	≤1.5kV	≤1.5kV	≤1.5kV	≤1.5kV	≤1.5kV
Max. backup fuse		125A gL				
Response time	tA	≤25ns				
Response time	tA(N-PE)	≤100ns				
Operating temperature range	Tu	-40°C~80°C				
Operating State/Fault Indication		Green/Red				
Cross-section area (Min.)		4mm ²				
Cross-section area (Max.)		35mm ²				
For mounting on		35mm Din rail				
Enclosure material		Thermal Plastic UL94-V0				
Degree of Protection		IP20				
No. of Poles		1P,2P(1P+N),3P,4P(3P+N),1+NPE,3+NPE				

Overall and Installation Dimension(mm)

