


## POLYCRYSTALLINE SILICON MODULE



**10** year  
product  
warranty

**25** year  
power output  
warranty


Address: Floor 17-18th, No.4 Building Zhuyu  
International Commercial. Center,  
No.9 Shouti South Road, Haidian  
District, Beijing 100048, China

Tel: +86-10-68796522

Fax: +86-10-68796522

E-mail: sales@cnbmsolar.com

Website: www.cnbmsolar.com



# 6P-325

## POLYCRYSTALLINE SILICON MODULE

### Products Characteristics



Widely using of the most popular and mature type of modules for on-grid system.



Leading manufacturing technology in PV industry, strictly controlling the quality of raw materials and the process of producing



100% EL inspection, ensures modules are defects free.



Cells binned by current to improve module performance



Anti reflective glass. Not only to increase the light absorption, but also to make the module has the function of self-cleaning in water environment, effectively reducing the power loss caused by dust.



Outstanding performance in low-light irradiance environments.



Excellent mechanical load resistance: Certified to withstand high wind loads(2400pa) and snow loads(5400pa).



High salt and ammonia resistance



Positive power tolerance: 0~+5w

### Warranty


- 10 year product warranty
- 10 year 90% of Min. rated output power, and 25 year 80% of Min. rated output power warranty

### Comprehensive Certificates



- ISO Certificate
- IEC61215、IEC61730 Certificate
- SGS-TUV Certificate
- CE Certificate

Specifications subject to technology and test conditions,

# 6P-325



## ▼ Engineering Drawings (Front Side)



Address: Floor 17-18th, No.4 Building Zhuyu  
International Commercial. Center,  
No.9 Shouti South Road, Haidian  
District, Beijing 100048, China  
Tel: +86-10-68796522  
Fax: +86-10-68796522  
E-mail: sales@cnbmsolar.com  
Website: www.cnbmsolar.com

## Raw Materials and Mechanical Parameters

6P-325	
Type of Cells(mm)	poly 78.375x156.75
NO. of Cells and Connections	6x24=144
Dimensions(mm)(L*W*H)	1965x992x40
Weight(kg)	22.9
Glass	3.2mm Tempered Glass
Encapsulation	EVA
Backsheet	Multilayer Composite
Aluminium-Frame	Silvery/Black Anodized aluminium alloy
Junction-Box	IP67/IP68
Cable	4mm <sup>2</sup> , 900mm
Connector	MC4 and MC4 Compatible
Package Configuration	26pcs/pallet
40GP	624pcs
40HQ	672pcs

## Performance Parameters

6P-325	
Maximum System Voltage	1000V
Operating Temperature	-45~+80℃
Maximum Series Fuse	20A
Maximum Static Load, Front Side (e.x. Snow, Wind)	5400PA
Maximum Static Load, Back Side (e.x. Wind)	2400PA
Application Grade	Class A

## Electrical Parameters (Standard Test Condition)

6P-325	
Rated Maximum Power(Mp)	325W
Power Tolerance	0 - +5W
Module Efficiency	18.10%
Open Circuit Voltage(Voc)	92.4V
Maximum Power Voltage(Vmp)	74.3V
Short Circuit Current(Isc)	4.67A
Maximum Power Current(Imp)	4.38A
Temperature Coefficient of Isc	+0.06%
Temperature Coefficient of Voc	-0.33%
Temperature Coefficient of Pmp	-0.45%
Standard Test Condition	Irradiance:1000W/M2, Cell Temperature:25℃, Spectrum AM:1.5

The Electrical Parameters of the module are the average theory figure under the standard test condition, each one exists difference. Can not be treated as the basis of module delivery.