

MPS microgrid series V 1.6

MPS microgrid hybrid inverter



KEY STRENGTHS

- Integrated MPPT module/transformer/STS/ maintenance bypass.
- Support 100% unbalance.
- Support parallel connection of multiple machines.
- Global launch of MPPT step-up/-down adaptive technology, supporting flexible configuration of PV capacity
- Support DG load rate control to improve fuel economy.
- Support flexible configuration of control strategies.

APPLICATIONS

 Off-grid mine

 Off-grid island

 Nomadic farm

 Villages without electricity



MPS0030/MPS0050



MPS0100/MPS0150



MPS0250



MPS0500

Model	MPS0030	MPS0050	MPS0100	MPS0150	MPS0250	MPS0500
AC(on-grid)						
Max. output power (kW)	33	55	110	165	275	550
Rated output power (kW)	30	50	100	150	250	500
Rated voltage(V)	400					
Voltage range (V)	320~460					
Rated current (A)	43	72	144	216	361	722
Rated frequency (Hz)	50/60					
Frequency range (Hz)	45~55/55~65					
THDi	<3%					
Power factor	1leading-1lagging(settable)					
Grid type	3W+N+PE					

AC(off-grid)						
Max. output power (kW)	33	55	110	165	275	550
Rated power (kW)	30	50	100	150	250	500
Rated voltage (V)	400					
Rated current (A)	43	72	144	216	361	722
THDu	≤1% linear; or ≤5% nonlinear					
Rated frequency (Hz)	50/60					
Overload capacity	110% long-term, 120% 1min					

PV input

Max. PV input voltage (V)	1,000					
Max. PV power (kW)	82.5	82.5	165/247.5	165/247.5/330	330/412.5	660/742.5/825
MPPT module quantity	1	1	2/3	2/3/4	4/5	8/9/10
MPPT voltage range (V)	250~1000					

Battery

Battery voltage range (V)	250~850	320~850	420~950	420~950	420~950	500~950
Max. charging power (kW)	33	55	110	165	275	550

General data

Dimension W*D*H (mm)	800*800*1,900	800*800*1,900	1,200*800*2,050	1,200*800*2,050	(600*720*2,050)*1+ 1,200*800*2,050	(600*720*2,050)*2+ 1,600*1,050*2,050
Weight (kg)	620	720	1,120/1,150	1,250/1,280/1,310	1,950/1,980	3,205/3,235/3,265
Operation temperature (°C)	-30 ~ 55					
Relative humidity	0 ~95% non-condensing					
Ingress protection	IP20					
Noise emission (dB)	<70					
Operating altitude (m)	>3,000 Derating					
Cooling	Air Cooling					

Display and communication

Display	LCD touch-screen					
BMS communication	RS485, CAN					
EMS communication	RS485, TCP/IP					
Certificates	EN 62109-1/-2, EN 62477-1, EN 61000-6-2/-6-4, NRS 097-2-1:2024, ASGC					